

TRITURADORA DE MOLINO ULTRAFINO



ESPECIFICACIONES TÉCNICAS

Modelo	HGM88	HGM95	HGM 100	HGM120	HGM130	HGM160	HGM175	HGM190
Tamaño de alim. (mm)	< 20	< 25	<25	< 25	< 25	< 30	< 35	<40
Tamaño del prod. final (mm)	0.25-0.015	0.25-0.015	0.25-0.015	0.25-0.015	0.25-0.038	0.25-0.038	0.25-0.038	0.25-0.038
Vel. rotacion de eje central (r.min)	167	150	142	136	105	82	75	74
Diametro del anillo pulverizador (mm)	908x160	1006x190	1075x200	1280x240	1400x240	1770x290	1900x300	2040x320
Diametro del rodillo pulverizador (mm)	270x160	300x190	320x200	370x240	410x240	450x290	500x300	640x325
Potencia del motor (kw)	Y225M 8-22	Y250M 8-30	Y225M 4-45	Y250M 4-55	Y280S 4-75	Y315M 4-132	Y315L1- 4-160	Y2-355L1 4-280
Potencia motor soplador (kw)	Y180L 4-22	Y200L 4-30	Y225M 4-45	Y280S 4-75	Y280M 4-90	Y315L1 4-160	Y315L2- 4-200	Y2-355L1 4-280
Potencia motor clasificador (kw)	Y132M2 6-6.55	Y160M 6-7.5	Y160L 6-11	Y180L 6-15	Y200L1 6-18.5	Y200L2-6-22 Y225M-6-30	Y225M-6-30 Y280S-6-45	Y250m 4-55